

## Plus-point product diversity

Standard tail lift for trucks and trailers, with a capacity of 2.500 kg at a load distance of 1.000 mm.

# Sörensen

The tail lift experts

## Our sturdy model: X1A 2500

Standard tail lift with a capacity of 2.500 kg



Particularly sturdy system for daily use in the food and beverage distribution, which can carry 2.500 kg at a load distance of 1.000 mm



Also available for semi-trailers and central axle trailers (X1AT 2500), featuring a telescopic assembly console.

## Your powerful partner with solid advantages:

- ✚ Consequent weight reduction while maintaining its stability and unmatched power reserves
- ✚ The platform can be tilted at any loading position
- ✚ Load distance of 1.000 mm
- ✚ Very high power reserves
- ✚ Cargo securing "Code XL" for a payload up to 10.000 kg included as standard
- ✚ Rear bumper according to the directive 2006/20/EG for an unlimited vehicle weight
- ✚ Low life cycle costs through compact design and maintenance-free bushings
- ✚ The nitrate surface treatment of the cylinders offers protection against corrosion

# Plus-point product diversity

Standard tail lift for trucks and trailers, with a capacity of 2.500 kg at a load distance of 1.000 mm.



## Product information

### + Lifting mechanism

Black KTL coated (RAL 9005), maintenance-free bushings, pre-drilled assembly plates to bolt the lift onto the vehicle frame, crash bar in one piece (tested by TÜV and EU-approved), electrical interface according to VEHH norms

### + Lifting capacity / load distance

2.500 kg at 1.000 mm

### + Loading height

Lifting arm length 750 mm/ loading height 1.300 mm max.  
Lifting arm length 875 mm/ loading height 1.430 mm max.

### + Platform

Aluminum, smooth back, for optimal advertising



Industrial components coming from european suppliers of the automotive industry ensure a very high level of quality.

## Standard equipment

- + Waterproof control box
- + Load distance of 1.000 mm
- + 2 button hand-held control with wanderlead
- + Installation ready steel mainframe, black coated, with brackets
- + SoftControl for soft tilt-up and tilt-down of the platform
- + Cargo securing "Code XL"
- + Controls for servicing the lift (Service Switch)
- + Quiet running power pack with thermo switch
- + Platform rolls
- + Maintenance-free bushings
- + Warning flags

TYPE:	X1A 2500	
	mm	kg
Platform / weight:	2.000	585
	2.100	595
	2.200	599
	2.300	608

TYPE:	X1AT 2500	
	mm	kg
Platform / weight:	2.000	694
	2.100	701
	2.200	708
	2.300	717

## Accessories (in extracts)

- + Warranty extension from 24 to 36 months
- + Flat 2 button safety foot controls on the platform
- + 3 button hand-held control with wanderlead
- + Warning flashlights on platform corners
- + Sealing kit
- + Hydraulic or mechanic support stands
- + Different types of cart stop
- + Control box fitted with a key switch
- + Noise reducing treatment of platform surface (KVS)
- + Pre-assembled battery box
- + Cross milling on the platform
- + Battery loading line for trailers or semi-trailers

The patented X1 Technology makes it possible:

- + Unrivaled light tail lifts, maximum stability for optimal loading capacity and efficient workflows.
- + Compact design, fewer construction parts - exclusively high quality - and maintenance-free bushings for minimum life cycle costs of the tail lift.

...lifts for life